

Printing date 17.03.2016 Version number 23 Revision: 17.03.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Osmo Country Color

Article number: 2101 White; 2203 Light Ochre; 2204 Ivory; 2205 Sunflower Yellow; 2308 Nordc Red;

2310 Cedar/Redwood; 2311 Signal Red; 2404 Fir Green; 2501 Labrador Blue; 2506 Royal Blue; 2507 Dove Blue; 2606 Medium Brown; 2607 Dark Brown; 2703 Charcoal; 2704 Dust Grey; 2708 Pebble Grey; 2716 Anthracite Grey; 2735 Light

Grey; 2742 Traffic Grey

1.2 Relevant identified uses of the substance or mixture and uses

advised against No further relevant information available.

Application of the substance / the

mixture Coating compound/ Surface coating/ paint

Paint

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG

Affhüppen Esch 12 D-48231 Warendorf

Further information obtainable

from: Product safety department

Phone: +49 (0) 251 / 692 - 188 Fax: +49 (0) 251 / 692 - 462 e-mail: helmut.starp@osmo.de

1.4 Emergency telephone

number: emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German

and English

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to

Regulation (EC) No 1272/2008 The product is not classified according to the CLP regulation.

2.2 Label elements

Labelling according to Regulation

(EC) No 1272/2008VoidHazard pictogramsVoidSignal wordVoidHazard statementsVoid

Precautionary statements Although this product is not subject to identification regulations, we recommend that

the safety suggestions are observed.

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

P271 Use only outdoors or in a well-ventilated area. P262 Do not get in eyes, on skin, or on clothing.

(Contd. on page 2)



Printing date 17.03.2016 Version number 23 Revision: 17.03.2016

Trade name: Osmo Country Color

(Contd. of page 1)

25-50%

Additional information: Observe the general safety regulations when handling chemicals.

Always wear a dust mask when sanding. Safety data sheet available on request.

Information concerning

particular hazards for human and

environment: Warning:

Wash out any used cloth impregnated with this product immediately after use or store

in an airtight container (danger of self-ignition)

2.3 Other hazards

Results of PBT and vPvB assessment

PBT:Not applicable.vPvB:Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

After inhalation: Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult

doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: If swallowed, seek medical advice immediately and show this container or label.

Induce vomiting only, if affected person is fully conscious.

4.2 Most important symptoms and

effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special

treatment needed No further relevant information available.

(Contd. on page 3)



Printing date 17.03.2016 Version number 23 Revision: 17.03.2016

Trade name: Osmo Country Color

(Contd. of page 2)

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant

foam.

For safety reasons unsuitable

extinguishing agents: Water with full jet

5.2 Special hazards arising from

the substance or mixture Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

Protective equipment: Mouth respiratory protective device.

Additional information Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official

regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and

emergency procedures Keep away from ignition sources.

Ensure adequate ventilation

6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for

containment and cleaning up: Warm water and cleansing agent

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

6.4 Reference to other sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Keep receptacles tightly sealed.

Keep away from heat and direct sunlight.

Use only in well ventilated areas. Prevent formation of aerosols.

Information about fire - and

explosion protection: Keep ignition sources away - Do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by

storerooms and receptacles: Store in a cool location.

(Contd. on page 4)



Printing date 17.03.2016 Version number 23 Revision: 17.03.2016

Trade name: Osmo Country Color

(Contd. of page 3)

Store only in the original receptacle.

Information about storage in one

common storage facility: Do not store together with alkalis (caustic solutions).

Do not store together with oxidising and acidic materials.

Further information about

storage conditions: Keep container tightly sealed.

Store receptacle in a well ventilated area.

Protect from frost.

Protect from heat and direct sunlight.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about

design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

64742-48-9 aliphatic hydrocarbons, C10-C13

TWA (8 H) Long-term value: 1.000 mg/m³, 150 ppm ppm

Source: UK SIA

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment: General protective and hygienic

measures: Immediately remove all soiled and contaminated clothing

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

Do not carry product impregnated cleaning cloths in trouser pockets.

Respiratory protection: Use suitable respiratory protective device only when aerosol or mist is formed.

Not necessary if room is well-ventilated.

Short term filter device:

Filter A/P2

Protection of hands: Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/

the preparation.

Selection of the glove material on consideration of the penetration times, rates of

diffusion and the degradation

Material of gloves Nitrile rubber, NBR

Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective

gloves and has to be observed.

(Contd. on page 5)



Printing date 17.03.2016 Version number 23 Revision: 17.03.2016

Trade name: Osmo Country Color

(Contd. of page 4)

For the permanent contact gloves made of the following materials

are suitable: Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

For the mixture of chemicals mentioned below the penetration time has to be at least

480 minutes (Permeation according to EN 374 Part 3: Level 6).

As protection from splashes gloves made of the following

materials are suitable: Nitrile rubber, NBR Eye protection: If risk of splashing:

Safety glasses according to EN 166:2001 (e.g. densely closing frame glasses with side

protection)

Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form: Fluid

Colour: According to product specification

Odour: Mild

Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: > 180 °C (DIN 51751)

Flash point: ≥ 63 °C (DIN 53213)

Ignition temperature: 240 °C

Self-igniting: Product is not selfigniting.

Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are

possible.

Explosion limits:

 Lower:
 0.6 Vol %

 Upper:
 7.0 Vol %

Vapour pressure: 3 hPa [20 °C]

Density at 20 °C: 1.05 - 1.30 g/cm³ (DIN 51757)

Solubility in / Miscibility with

water: Not miscible or difficult to mix.

(Contd. on page 6)



Printing date 17.03.2016 Version number 23 Revision: 17.03.2016

Trade name: Osmo Country Color

(Contd. of page 5)

Viscosity:

Dynamic:

Not determined. 40-80 s (DIN 53211/4)

Kinematic at 20 °C:

>21 mm²/s (40 °C)

Solvent separation test:

< 3 % (ADR 2.2.1.4f)

Solvent content:

VOC (EC)

< 400 g/l (VOC-max. Cat A/e (2010) = 400 g/l)

9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity

No further relevant information available.

10.2 Chemical stability

Thermal decomposition /

conditions to be avoided:

No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous reactions

Reacts with fabric soaked in the product (e.g. cleaning wool).

Reacts with acids, alkalis and oxidising agents.

No further relevant information available.

No further relevant information available.

10.4 Conditions to avoid

10.5 Incompatible materials:

10.6 Hazardous decomposition

products:

Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

Additional information:

Warning:

Wash out any used cloth impregnated with this product immediately after use or store

in an airtight container (danger of self-ignition)

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

64742-48-9 aliphatic hydrocarbons, C10-C13

Oral	LD50	> 5000 mg/kg (rat) (OECD 401)
Dermal		> 5000 mg/kg (rat) (OECD 402)
Inhalative	LC50 / 4h	21 mg/l (rat) (OECD 403)

Primary irritant effect:

Skin corrosion/irritation At long or repeated contact with skin it may cause dermatitis due to the degreesing

effect of the solvent.

(Contd. on page 7)



Printing date 17.03.2016 Version number 23 Revision: 17.03.2016

Trade name: Osmo Country Color

(Contd. of page 6)

Serious eye damage/irritation Based on available data, the classification criteria are not met. **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity
Based on available data, the classification criteria are not met.

Reproductive toxicity
Based on available data, the classification criteria are not met.

STOT-single exposure
Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

STOT-repeated exposure
Based on available data, the classification criteria are not met.

Aspiration hazard
Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:		
64742-48-9 aliphatic hydrocarbons, C10-C13		
EC50 / 48h	> 1000 mg/l (daphnia) (OECD 202)	
EC50/72h	> 1000 mg/l (algae) (OECD 201)	
LC50 / 96h	> 1000 mg/l (fish) (OECD 203)	
Biolog. Abbaubarkeit	(-) (leicht abbaubar)	

12.2 Persistence and degradability No further relevant information available.
12.3 Bioaccumulative potential No further relevant information available.
12.4 Mobility in soil No further relevant information available.

Additional ecological information:

General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for

water

Do not allow product to reach ground water, water course or sewage system.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable. *vPvB:* Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation Must not be disposed together with household garbage. Do not allow product to reach

sewage system.

	Europear	waste catalogue	l
	08 01 11	waste paint and varnish containing organic solvents or other dangerous substances	l
Į	15 01 10	packaging containing residues of or contaminated by dangerous substances	

(Contd. on page 8)



Printing date 17.03.2016 Version number 23 Revision: 17.03.2016

Trade name: Osmo Country Color

(Contd. of page 7)

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14:	Transport	information
-------------	-----------	-------------

14.1 UN-Number	
ADR, ADN, IMDG, IATA	Void
14.2 UN proper shipping name	
ADR, ADN, IMDG, IATA	Void
14.3 Transport hazard class(es)	
ADR, ADN, IMDG, IATA	
Class	Void
14.4 Packing group	
ADR, IMDG, IATA	Void
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Not applicable.
14.7 Transport in bulk according to Annex II	I of Marpol
and the IBC Code	Not applicable.
Transport/Additional information:	Not dangerous according to the above specifications.
UN "Model Regulation":	Void

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations:

VOC(EC) < 400 g/l (VOC-max. Cat A/e (2010) = 400 g/l)

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases H304 May be fatal if swallowed and enters airways.

Department issuing MSDS: product safety department

Contact: Hr. Dr. Starp

(Contd. on page 9)



Printing date 17.03.2016 Version number 23 Revision: 17.03.2016

Trade name: Osmo Country Color

(Contd. of page 8)

Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement

concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Asp. Tox. 1: Aspiration hazard, Hazard Category 1

* Data compared to the previous version altered.

GB