



CHOPPING BOARD OIL HIGH SOLID

Oil-wax wood finish



3099
Clear Matt

PRODUCT DESCRIPTION

Clear oil-wax combination for wooden chopping boards. Osmo Chopping Board Oil is based on natural plant oils and waxes. Suitable for wood; microporous surface will not crack, peel, flake or blister. Resistant against wine, beer, cola, coffee, tea, fruit juice, milk and water in accordance with German DIN 68861-1A – no water spots. The dry finish is safe for humans, animals and plants (resistant to saliva and perspiration acc. German DIN 53160).

Osmo Chopping Board Oil is food safe acc. EN 1186 Part 5 / 14.

RECOMMENDED USE

Osmo Chopping Board Oil is ideal for the protection of wooden chopping boards surfaces.

INGREDIENTS

Based on natural plant oils and waxes (sunflower oil, soybean oil, thistle oil, carnauba wax and candelilla wax), paraffin, lead-free siccatives (drying agents) and water-repellent additives. Dearomatized white spirit (benzene-free). VOC classification in compliance with EU regulations (2004/42/EC): out of scope. Detailed declaration of ingredients available upon request.

TECHNICAL DATA

Specific gravity: 0.92-0.97 g/cm³
Viscosity: 50-70s DIN EN ISO 2431/4 mm, thixotropic
Odour: faint/mild, after drying odourless
Flash point: >60°C acc. DIN EN ISO 2719

STORAGE

Up to 5 years and longer if container is kept dry and closed tightly. If thickened by frost, store for 24-36 hours at room temperature before use.



SURFACE PREPARATION

Wood surface must be clean, dry and frost-free (moisture content max. 18%).

Osmo Chopping Board Oil is ready to use. Do not thin. Stir well before use.

Clean old microporous stains thoroughly. Old paints and lacquers must be completely removed. As a general rule, wear a dust mask during sanding works. Fill small cracks, larger joints or holes in wood (with Osmo Wood Filler).

Sand wood surfaces carefully. Begin with coarse sandpaper – final sanding work P150-240 (depending on wood species). Before oiling the surface, remove sanding dust with a broom or vacuum cleaner.

The finished surface is influenced by several factors, including the condition of the wood. Therefore, a trial application is always required, especially for unfamiliar surfaces.

METHODS OF APPLICATION

Apply the first coat thinly along the wood grain with an Osmo Microfibre Roller, Flat Brush or Oil Finish Applicator Fleece.

Allow to dry for approx. 8-10 hours. Ventilate well while drying.

Apply the second coat with an Osmo Oil Finish Applicator Fleece or a lint-free cloth.

For renovations, one coat applied to the clean and dry surface with an Oil Finish Applicator Fleece or lint-free cloth is usually sufficient.

CLEANING OF TOOLS

With Osmo Brush Cleaner (free of aromatic compounds).



DRYING TIME

Approx. 8-10 hours (normal climatic conditions, 23 °C/ 50 % rel. humidity). Lower temperatures and/or higher air humidity can increase the drying time. Ventilate well while drying.

COVERAGE

1 litre covers approx. 24 m² with one coat.
Coverage depends significantly on the condition of the wood. All information refers to smooth and planed/sanded surfaces. Other surfaces may lead to differences in coverage.

NOTE

Osmo Chopping Board Oil Clear enhances the tone of wood (permanent wet effect). Applying the product too generously and insufficient ventilation lead to delays in drying time. Surfaces treated with Osmo Chopping Board Oil can be cleaned effortlessly with a damp cloth; afterwards rub dry.

CAUTION

Keep out of reach of children. Do not get in eyes, on skin, or on clothing. If medical advice is needed, have product container or label at hand. Use only outdoors or in a well-ventilated area. Warning: Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition). The dried finish is classified as B2 (normal flammability) according to DIN 4102 regulations. Safety data sheet available on request.

DISPOSAL

Dispose of leftover product and completely emptied packaging according to local official guidelines (waste code number 08 01 11). Only completely emptied cans can be recycled.

COLOUR TONES

3099 Clear Matt

CAN SIZES

0,5 L

The above mentioned information is provided to the best of our knowledge however without any liability.

Version 11/18