

# Magnetic drill - low profile

# ECO.36



HEIGHT MEASURES JUST

**165 mm / 6 1/2"**



## Key specifications

<b>Cutters</b>	<b>In-corner</b>	<b>Height</b>
<b>36 mm</b>	<b>50 mm</b>	<b>165 mm</b>
<b>1 7/16"</b>	<b>2"</b>	<b>6 1/2"</b>
<b>Weight</b>	<b>Motor</b>	<b>Magnet</b>
<b>10.3 kg</b>	<b>1050 W</b>	<b>1200 kg</b>
<b>22.7 lbs</b>	<b>9.6 A</b>	<b>2645 lbs</b>

## Technical data

	<b>Metric</b>	<b>Imperial</b>
Annular cutters	Ø 36 mm	1 7/16"
Countersink	Ø 40 mm	1 9/16"
In-corner drilling	0°: 50 mm	2"
	90°: 53 mm	2 1/16"
	45°: 60 mm	2 3/8"
Length	310 mm	12 3/16"
Width	135 mm	5 5/16"
Height	165 mm	6 1/2"
Stroke	40 mm	1 9/16"
Weight	10.3 kg	22.7 lbs
Magnet (lxwxh)	80x160 mm	3 1/8"x6 5/16"
Magnetic force	1200 kg	2645 lbs
Motor power	1050 W	9.6 A
Speed (no load)	700 min <sup>-1</sup>	700 rpm
Speed (load)	400 min <sup>-1</sup>	400 rpm
	(1050 W)	(9.6 A)
Spindle	19,05 mm weldon	3/4" weldon
Voltage	110 - 120 V AC / 50-60 Hz	
	220 - 240 V AC / 50-60 Hz	

## Additional benefits:

- User-friendly quick-connect cutter fitment system
- Detachable ratchet feed handle for left and right use
- Removeable and slidable up and down safety guard
- Integrated motor cable
- Safety strap attachment integrated

