

Safety Data Sheet

in accordance with HSNO

Printing date 15.10.2019

Version number 1.4

Revision: 15.10.2019

SECTION 1: Identification of the substance or mixture and of the supplier

1.1 Product identifier

Trade name: Osmo Polyx®-Oil Express

Article number: 3332 Clear Satin
3362 Clear Matt

1.2 Relevant identified uses of the substance or mixture

and uses advised against No further relevant information available.

Application of the substance

/ the mixture Coating compound/ Surface coating/ paint

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG
Affhüppen Esch 12
D-48231 Warendorf

Further information obtainable from:

Product safety department
Tel.: +49 (0) 251 / 692 - 188
Fax: +49 (0) 251 / 692 - 462
e-mail: helmut.starp@osmo.de

1.4 Emergency telephone

number: National Poison Centre: 0800 764 766 (0800 POISON)
Chemcall 24/7 Emergency Response Service: 0800 243 622 (0800 CHEMCALL)
Emergency Services (Fire, Ambulance, Police): Dial 111

Importer

Osmo NZ Ltd.
218H Marua Road
Mt Wellington
AUCKLAND 1051
Phone: +64 (0) 9 951 6010
Email: info@osmo.co.nz

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Acute Tox. 5 H333 May be harmful if inhaled.

Additional information: HSNO Classes: 3.1C, 6.1E

2.2 Label elements

Hazard pictograms



GHS02

Signal word

Warning

(Contd. on page 2)

Safety Data Sheet

in accordance with HSNO

Printing date 15.10.2019

Version number 1.4

Revision: 15.10.2019

Trade name: Osmo Polyx®-Oil Express

(Contd. of page 1)

Hazard statements

H226 Flammable liquid and vapour.

H333 May be harmful if inhaled.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from flames and hot surfaces. No smoking.

P262 Do not get in eyes, on skin, or on clothing.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P312 IF INHALED: Call a POISON CENTER/doctor if you feel unwell.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with national regulations.

2.3 Other hazards

Observe the general safety regulations when handling chemicals.

Always wear a dust mask when sanding.





Warning:

Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition)

Results of PBT and vPvB assessment**PBT:** Not applicable.**vPvB:** Not applicable.

SECTION 3: Composition/Information on ingredients

3.2 Mixtures**Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

CAS: 64742-48-9	aliphatic hydrocarbons, C10-C13	25–50%
EC number: 918-481-9	 Asp. Tox. 1, H304; Flam. Liq. 4, H227	
CAS: 64742-49-0	aliphatic hydrocarbons, C9-C10	10–25%
EC number: 927-241-2	 Flam. Liq. 3, H226;  Asp. Tox. 1, H304;  STOT SE 3, H336; Acute Tox. 5, H303; Acute Tox. 5, H313; Acute Tox. 5, H333	

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures**General information:** Immediately remove any clothing soiled by the product.
Take affected persons out into the fresh air.

(Contd. on page 3)

Safety Data Sheet

in accordance with HSNO

Printing date 15.10.2019

Version number 1.4

Revision: 15.10.2019

Trade name: Osmo Polyx®-Oil Express

(Contd. of page 2)

- After inhalation:** Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact:** Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing:** If swallowed, seek medical advice immediately and show this container or label.
Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Headache
Dizziness

4.3 Indication of any

immediate medical attention

and special treatment needed No further relevant information available.

SECTION 5: Fire fighting measures

5.1 Extinguishing media

Suitable extinguishing

agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable

extinguishing agents:

Water with full jet

5.2 Special hazards arising

from the substance or

mixture

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

Protective equipment:

Mouth respiratory protective device.

Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.
Keep away from ignition sources.
Ensure adequate ventilation

(Contd. on page 4)

Safety Data Sheet

in accordance with HSNO

Printing date 15.10.2019

Version number 1.4

Revision: 15.10.2019

Trade name: Osmo Polyx®-Oil Express

(Contd. of page 3)

6.2 Environmental**precautions:**

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for**containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

Ensure adequate ventilation.

Warm water and cleansing agent

6.4 Reference to other**sections**

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe**handling**

Keep receptacles tightly sealed.

Use only in well ventilated areas.

Keep away from heat and direct sunlight.

Prevent formation of aerosols.

Information about fire - and**explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities**Storage:****Requirements to be met by****storerooms and receptacles:**

Store only in the original receptacle.

Store in a cool location.

Information about storage in**one common storage facility:**

Do not store together with alkalis (caustic solutions).

Do not store together with oxidising and acidic materials.

Further information about**storage conditions:**

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Storage class:

3

7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about**design of technical facilities:**

No further data; see item 7.

(Contd. on page 5)

Safety Data Sheet

in accordance with HSNO

Printing date 15.10.2019

Version number 1.4

Revision: 15.10.2019

Trade name: Osmo Polyx®-Oil Express

(Contd. of page 4)

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Additional information:

The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.
Do not carry product impregnated cleaning cloths in trouser pockets.
Keep away from foodstuffs, beverages and feed.
Do not inhale gases / fumes / aerosols.

Respiratory protection:

Use suitable respiratory protective device only when aerosol or mist is formed. Not necessary if room is well-ventilated.
Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
Half mask with round thread connection EN 148-1 (screw-on filter) and combination filter A1 - P2 according to German DIN EN 14387.

Protection of hands:

Protective gloves
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Nitrile rubber, NBR
Recommended thickness of the material: ≥ 0.4 mm
For the mixture the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Eye protection:

Tightly sealed goggles

(Contd. on page 6)

Safety Data Sheet

in accordance with HSNO

Printing date 15.10.2019

Version number 1.4

Revision: 15.10.2019

Trade name: Osmo Polyx®-Oil Express
Body protection: Protective work clothing

(Contd. of page 5)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form:	Fluid
Colour:	Grey
Odour:	Mild

Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	Undetermined.

Flash point: 30-35 °C (DIN EN ISO 2719)

Auto-ignition temperature: Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Explosion limits:

Lower:	0.6 Vol %
Upper:	7.0 Vol %

Vapour pressure at 20 °C: 10 hPa
Not determined.

Density at 20 °C: 0.88-0.95 g/cm³ (DIN 51757)

Solubility in / Miscibility with water: Not miscible or difficult to mix.

Viscosity:

Dynamic:	Not determined.
Kinematic at 20 °C:	20-25 s (DIN EN ISO 2431/4mm)
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions

 Reacts with fabric soaked in the product (e.g. cleaning wool).
Self igniting.

(Contd. on page 7)

Safety Data Sheet

in accordance with HSNO

Printing date 15.10.2019

Version number 1.4

Revision: 15.10.2019

Trade name: Osmo Polyx®-Oil Express

(Contd. of page 6)

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous
decomposition products: Carbon monoxide and carbon dioxide
Nitrogen oxides (NO_x)

Additional information:

Warning:

Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition)

SECTION 11: Toxicological information

11.1 Information on toxicological effects
Acute toxicity May be harmful if inhaled.

LD/LC50 values relevant for classification:
64742-48-9 aliphatic hydrocarbons, C10-C13

Oral LD50 >5,000 mg/kg (rat)

Dermal LD50 >5,000 mg/kg (rat)

Inhalative LC50 / 4h >5 mg/l (rat)

64742-49-0 aliphatic hydrocarbons, C9-C10

Oral LD50 >2,000 mg/kg (rat)

Dermal LD50 >2,000 mg/kg (rat)

Inhalative LC50 / 4h >20 mg/l (rat)

34590-94-8 Dipropylene glycol monomethyl ether

Oral LD50 >5,000 mg/kg (rat)

Dermal LD50 >19,020 mg/kg (rat)

13,000–14,000 mg/kg (rabbit)

Inhalative LC50 / 4h 1,667 mg/l (rat)

LC50 / 72h 0.76 mg/l (senastrum capricornutum)

Primary irritant effect:
Skin corrosion/irritation At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin
sensitisation Based on available data, the classification criteria are not met.

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

(Contd. on page 8)

Safety Data Sheet

in accordance with HSNO

Printing date 15.10.2019

Version number 1.4

Revision: 15.10.2019

Trade name: Osmo Polyx®-Oil Express

(Contd. of page 7)

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity**Aquatic toxicity:****64742-48-9 aliphatic hydrocarbons, C10-C13**

EC50 / 48h	>1,000 mg/l (daphnia)
IC50 / 72h	>1,000 mg/l (algae)
LC50 / 96h	>1,000 mg/l (fish)

64742-49-0 aliphatic hydrocarbons, C9-C10

EC50 / 24h	<130 mg/kg (Oncorhynchus mykiss (Regenbogenforelle)) >100 mg/kg (selenastrum capricornutum)
------------	--

34590-94-8 Dipropylene glycol monomethyl ether

EC50 / 48h (Static)	1,919 mg/l (daphnia)
LC50 / 96h	5.3 mg/l (Oncorhynchus mykiss (Regenbogenforelle))
LC50 / 48h	10.2 mg/l (Oncorhynchus mykiss (Regenbogenforelle))

12.2 Persistence and degradability

No further relevant information available.

12.3 Bioaccumulative potential

No further relevant information available.

12.4 Mobility in soil

No further relevant information available.

Additional ecological information:**General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

12.5 Results of PBT and vPvB assessment**PBT:**

Not applicable.

vPvB:

Not applicable.

12.6 Other adverse effects

No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods**Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:**Recommendation:**

Disposal must be made according to official regulations.

(Contd. on page 9)

Safety Data Sheet
in accordance with HSNO

Printing date 15.10.2019

Version number 1.4

Revision: 15.10.2019

Trade name: Osmo Polyx®-Oil Express

(Contd. of page 8)

SECTION 14: Transport information

14.1 UN-Number
ADR, IMDG, IATA

UN1263

14.2 UN proper shipping name

ADR

1263 PAINT

IMDG, IATA

PAINT

14.3 Transport hazard class(es)

ADR**Class**

3 (F1) Flammable liquids.

Label

3

IMDG, IATA**Class**

3 Flammable liquids.

Label

3

14.4 Packing group

ADR, IMDG, IATA

III

14.5 Environmental hazards:

Marine pollutant:

No

14.6 Special precautions for user

Warning: Flammable liquids.

Danger code (Kemler):

30

EMS Number:

F-E, S-E

Stowage Category

A

14.7 Transport in bulk according to Annex II of

Marpol and the IBC Code

Not applicable.

Transport/Additional information:

ADR**Limited quantities (LQ)**

5L

Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

Transport category

3

Tunnel restriction code

D/E

IMDG**Limited quantities (LQ)**

5L

Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 10)

Safety Data Sheet

in accordance with HSNO

Printing date 15.10.2019

Version number 1.4

Revision: 15.10.2019

Trade name: Osmo Polyx®-Oil Express

(Contd. of page 9)

UN "Model Regulation":

UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

New Zealand Inventory of Chemicals

All ingredients are listed.

Directive 2012/18/EU

Named dangerous

substances - ANNEX I

None of the ingredients is listed.

Seveso category

P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower- tier requirements

5,000 t

Qualifying quantity (tonnes) for the application of upper- tier requirements

50,000 t

15.2 Chemical safety

assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.
 H227 Combustible liquid.
 H303 May be harmful if swallowed.
 H304 May be fatal if swallowed and enters airways.
 H313 May be harmful in contact with skin.
 H333 May be harmful if inhaled.
 H336 May cause drowsiness or dizziness.

Department issuing SDS:

product safety department

Contact:

Hr. Dr. Starp

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 LC50: Lethal concentration, 50 percent

(Contd. on page 11)

Safety Data Sheet
in accordance with HSNO

Printing date 15.10.2019

Version number 1.4

Revision: 15.10.2019

Trade name: Osmo Polyx®-Oil Express

(Contd. of page 10)

LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Flam. Liq. 4: Flammable liquids – Category 4
Acute Tox. 5: Acute toxicity – Category 5
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1

*** Data compared to the
previous version altered.**